

BLACK AND WHITE IMAGERUNNER LBP3580

PRODUCT SPECIFICATIONS

Model Name	imageRUNNER LBP3580
Type	Desktop Laser Printer Printing Method: Electrophoto Method (RAPID Fusing System)
Developing System	Contact Developing System Standard PDL: UFR II, PCL 5e/6, Adobe PostScript 3
Image Server Memory	Standard/Maximum: 768MB RAM CPU: ARM11-528MHz + ARM9-264MHz
Network Interface Connection	Shared 10/100/1000Base-T (RJ-45)
Other Interface	USB Hi-Speed (Device) x1 USB Hi-Speed (Host) x2 User Interface: LCD 22 Characters x 5 Lines 8 LED Indicators 12 Operation Keys
Printing Resolution	UFR II, PCL 5e/6, PostScript 3: 600 x 600 dpi, 1200 x 1200 dpi Equivalent, 2400 Equivalent x 600 dpi Engine: 600 x 600 dpi

BLACK AND WHITE IMAGERUNNER LBP3580

Print Drivers: UFR II, PCL 5e/6, PostScript 3: Windows® (XP/Windows Vista®/Windows 7/Windows 8/Server 2003/Server 2008/Server 2008 R2/Small Business Server 2011/Server 2012), Windows Terminal Servers (Server 2003/Server 2008/Server 2008 R2/Small Business Server 2011), Microsoft® Failover Cluster (Server 2003/Server 2008/Server 2008 R2), Citrix (Presentation Server 4.5, XenApp 5.0/6.0/6.5, XenDesktop 4.0/5.0/5.5/5.6), Macintosh® (OS X 10.5.8 or later), VMware (vSphere 4, 5), SAP (PCL 5e/6, PostScript 3 only)

Halftone 256 Gradations (Continuous-Tone)

Letter (BW): Up to 42 ppm

First Copy Time 8.5 Seconds

Maximum Original Size Legal (8-1/2" x 14")

Standard Paper Capacity 500-sheet Paper Cassette (20 lb. Bond) 100-sheet Multi-Purpose Tray

Optional 500-sheet Paper Cassette (Up to 2)

Maximum Paper Capacity 1,600 Sheets

Output Paper Capacity Face-down

Paper Output: Face-down/Face-up

BLACK AND WHITE IMAGERUNNER LBP3580

Output Tray: Approx. 250 Sheets Face-up Output Slot:
Approx. 50 Sheets

Output Sizes

Cassette Legal, Letter, Executive, Custom Sizes (Width: 4-1/8" to 8-1/2"; Length: 5-7/8" to 14")

Bypass Legal, Letter, Executive, Index Card, Custom Sizes (Width: 3" to 8-1/2"; Length: 5" to 14") and Envelopes

Acceptable Paper Weights

Cassette 16 lb. Bond to 32 lb. Bond (60 - 120g/m²)

Bypass 16 lb. Bond to 53 lb. Bond (60 - 199g/m²)

Duplexing

Duplexing Standard Automatic Trayless Duplexing (Legal, Letter)

Warm Up Time 28 Seconds or Less

Power Requirements 120-127V, 60Hz

Power Consumption (Approx., Average): Operating: 700W

BLACK AND WHITE IMAGERUNNER LBP3580

Standby: 14W

Deep Sleep Mode: Approx. 0.9W

Plug NEMA 5-15P

Dimension 13-5/8" x 17-7/8" x 16-3/4" (345mm x 454mm x 424mm)

Installation Space 17-7/8" x 28-1/4" (454mm x 622mm) (when Multi-Purpose Tray is extended)

Weight Approx. 36.6 lb. (16.6kg)*

SUPPLIES

Estimated Toner Yield Black (Starter): 6,000 Standard Pages**
Black: 12,500 Standard Pages**

ACCESSORIES

FEEDERS

Description **Paper Feeder Unit PF-45 (Optional)**

Acceptable Originals Legal, Letter, Executive, Statement, Custom Sizes (Width: 4-1/8" to 8-1/2" Length: 5-7/8" to 14")

Capacity 500 Sheets (20 lb. Bond)

Dimensions 5-5/8" x 17-7/8" x 18-1/2" (141mm x 454mm x 470mm)

BLACK AND WHITE IMAGERUNNER LBP3580

Weight

Approx. 12.1 lb. (5.5kg)

Other Optional Accessories

- SD Card-B1 (8GB)
- Barcode Printing Kit-F1

* Excluding the the toner cartridges.

** Toner cartridge yield in accordance with ISO/IEC 19752.

◆ Up to two Paper Feeder Units can be added.