

COLOR IMAGERUNNER LBP5280

PRODUCT SPECIFICATIONS

Model Name	Color imageRUNNER LBP5280
Type	Desktop Laser Printer Printing Method: Electrophoto Method (RAPID Fusing System)
Developing System	Contact Developing System
Image Server Memory	Standard 768MB RAM CPU: ARM11-528 MHz + ARM9-264 MHz
Printing Resolution	UFR II/PCL 5e/6/PS 3: 600 x 600 dpi 2400 (Equivalent) x 600 dpi Engine: 600 x 600 dpi
Halftone	256 Gradation (Continuous-Tone)
Letter	(B/W, Color): Up to 21 ppm (Letter)
First Copy Time	16 seconds or less
Maximum Original Size	Legal (8-1/2" x 14")

COLOR IMAGERUNNER LBP5280

Standard Paper Capacity 250 Sheet Paper Cassette (20 lb. Bond)

Optional: 250 Sheet Paper Cassette

Manual Bypass 50 Sheet Multi-Purpose Tray

Maximum Paper Capacity 550 Sheets

Output Sizes

Cassette Legal, Letter, Executive, Statement, Foolscap, Index Card, Envelope DL, Envelope COM-10, Envelope ISO-C5, Envelope ISO-B5, and Envelope Monarch, Custom Sizes (Width 4-1/8" to 8-1/2", Length 5-7/8" to 14")

Bypass Legal, Letter, Executive, Statement, Foolscap, Index Card, Envelope ISO-C5, Envelope ISO-B5, and Envelope Monarch, Custom Sizes (Width 3" to 8-1/2", Length 5" to 14")

Acceptable Paper Weights

Cassette 60 - 176 g/m² (16 lb. Bond to 43 lb. Bond)

Bypass 60 - 176 g/m² (16 lb. Bond to 47 lb. Bond)

Duplexing Standard Automatic Trayless Duplexing (Legal, Letter)

Paper Output: Face Down

COLOR IMAGERUNNER LBP5280

Output Capacity: Face Down Output Tray: Approx. 125 Sheets

Warm Up Time 29 seconds or less

Power Requirements 120-127V, 60Hz

Plug: NEMA 5-15P

Power Consumption: Operating: 440W

Stand By: 22W

Deep Sleep Mode: 1W

Dimension 13-5/8" x 16-5/16" x 19-3/4" (350mm x 414mm x 499mm)

Installation Space (H x W x D): 13-5/8" x 16-5/16" x 42-1/8"
(350mm x 414mm x 1069mm)

Weight Approx. 49.4 lb.(22.4 kg)*

SUPPLIES

Estimated Toner Yield Black (Starter): 3,400 images (1,200 images)**

Y/M/C Starter: 2,900 images (1,400 images)**

ACCESSORIES

FEEDERS

Description Paper Feeder Unit PF-701

COLOR IMAGERUNNER LBP5280

Acceptable Originals	Legal, Letter, Executive, Statement, Foolscap, Index Card, Envelope DL, Envelope COM-10, Envelope ISO-C5, Envelope ISO-B5, and Envelope Monarch, Custom Sizes (Width 4-3/16" to 8-1/2" . , Length 5-7/8" to 14".)
Capacity	250 Sheets (20 lb. Bond)
Dimensions	4-15/16" x 16-1/8" x 20-1/2" (115mm x 409mm x 520mm)
Weight	Approx. 12.1 lb.(4 kg)

OUTPUT OPTIONS

Print Board

PDL Support

(Standard): UFR II, PCL5c/6, Adobe PostScript 3

BAUER OFFICE SOLUTIONS

UFR II, PCL 5c/6, Adobe PS3: Windows® (XP/Windows Vista®/ Windows 7/Server 2003/Server 2008/ Server 2008 R2/Small Business Server 2011), Windows Terminal Servers (Server 2008/Server 2008 R2), Small Business Server 2011, Microsoft Failover Cluster (Windows Server 2003/Server 2003 R2/Server 2008/Server 2008 R2), Citrix (Presentation Server 4.5, XenApp 5.0/6.0/6.5, XenDesktop 2.0/2.1/3.0/4.0/5.0/5.5), Macintosh (OS X 10.4.9 or later) (UFR II/PS only), VMware (vSphere 4/5), SAP (PCL/PS only)

Interface Connections

Shared 10BASE-T/100BASE-TX/1000BASE-T

Other Interface: USB(Device)x1 / USB(Host)x2

COLOR IMAGERUNNER LBP5280

User Interface: LCD 22 Characters x 5 Line, 8 LED Indicators, 12 Operation Keys

* Excluding the CRG.

** Toner cartridge yield in accordance with ISO/IEC 19798

◆ One Paper Feeder Unit can be added.

