

# COLOR IMAGERUNNER LBP5480

## PRODUCT SPECIFICATIONS

Model Name	Color imageRUNNER LBP5480
Type	Desktop Laser Printer  <b>Printing Method:</b> Electrophoto Method (Color RAPID Fusing System)
Developing System	Contact Developing System
Image Server Memory	Standard/Maximum 768MB RAM  <b>CPU:</b> ARM11-528 MHz + ARM9-264 MHz
Network Interface Connection	Shared 10Base-T/100Base-TX/1000Base-T (Device)
Other Interface	USB Hi-Speed (Device) x1 / USB Hi-Speed (Host) x2  <b>User Interface:</b> LCD 22 Characters x 5 Lines, 8 LED Indicators, 12 Operation Keys
Printing Resolution	UFR II, PCL 5c/6, PostScript 3: 600 x 600 dpi, 9600 dpi equivalent x 600 dpi  Engine: 600 x 600 dpi  <b>Print Drivers:</b> UFR II, PCL 5c/6, PostScript 3: Windows®

## COLOR IMAGERUNNER LBP5480

(XP/Windows Vista®/Windows 7/Windows 8/Server 2003/Server 2008/ Server 2008 R2/Small Business Server 2011/Server 2012), Windows Terminal Servers (Server 2003/Server 2008/Server 2008 R2/Small Business Server 2011, Server 2012), Microsoft® Failover Cluster (Server 2003/Server 2008/Server 2008 R2),Citrix (Presentation Server 4.5, XenApp 5.0/6.0/6.5, XenDesktop 4.0/5.0/5.5/5.6), Macintosh® (OS X 10.5.8 or later) (UFR II/ PostScript 3 only), VMware (vSphere 4, 5), SAP (PCL 5c/6, PostScript 3 only)

Halftone 256 Gradations (Continuous-Tone)

Letter (BW/Color): Up to 33 ppm

First Copy Time BW printing: 10.2 Seconds or Less

Color printing: 10.4 Seconds or Less

Maximum Original Size Legal (8-1/2" x 14")

Standard Paper Capacity 500-sheet Paper Cassette (20 lb. Bond) 100-Sheet Multi-Purpose Tray

100-sheet Multi-Purpose Tray

Optional 500-sheet Paper Cassette

Maximum Paper Capacity 1,100 Sheets



# COLOR IMAGERUNNER LBP5480

Output Paper Capacity

Face-down Output Tray: Approx. 250 sheets

**Paper Output:** Face-down

Duplexing

Duplexing

Standard Automatic Trayless Duplexing (Legal, Letter)

Paper Size

**Drawer:** Standard Sizes: Letter, Executive,\*\* Statement  
Custom Sizes: In case of portrait orientation (only when the UFR II printer driver is used): Short edges 5-7/8" to 8-1/2"; Long edges 5-7/8" to 8-1/2" In case of landscape orientation: Short edges 4" to 8-1/2" \*\*\*; Long edges 5-7/8 to 11-5/8" \*\*\*

**Drawer:** Standard Sizes: Legal, Letter, Executive, Foolscap, and 16K Custom Sizes: In case of portrait orientation (only when the UFR II printer driver is used): Short edges 8-1/4" to 8-1/2"; Long edges 8-1/4" to 8-1/2" In case of landscape orientation: Short edges 5-7/8" to 8-1/2"; Long edges 8-1/4" to 14"

**Multi-Purpose Tray:** Standard Sizes: Legal, Letter, Executive, Statement, Foolscap, 16K, Index Card, Envelope (DL, No. 10, ISO-C5, and Monarch) Custom Sizes: In case of portrait orientation (only when the UFR II printer driver is used): Short edges 5" to 8-1/2"; Long edges 5" to 8-1/2" In case of landscape orientation: Short edges 3" to 8-1/2"; Long edges 5" to 14"

Paper Weight

**Cassette:** 16 lb. Bond to 43 lb. Bond (60 - 163 g/m2)

**Multi-Purpose Tray:** 16 lb. Bond to 80 lb. / Cover (60 - 216 g/m2)



# COLOR IMAGERUNNER LBP5480

\* Excluding the toner cartridges.

\*\* When width is 8-1/2", max length is 11".

\*\*\* When length is 11-5/8", max width is 8-1/4".

\*\*\*\* Toner cartridge yield in accordance with ISO/IEC 19798.

◆ One Paper Feeder Unit can be added.