

PRODUCT SPECIFICATIONS

Printer Type	5-Color 36-inch Printer
Number of Nozzles	Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each
Nozzle Pitch	1,200 dpi Non-firing nozzle detection and compensation
Print Resolution (Up to)	2,400 x 1,200 dpi (Max)
OS Compatibility	Windows® (XP/Vista/7/8.1/10) Mac (OS10.6.8-10.10x) ^a
Standard Interfaces	USB 2.0 High-Speed 10/100/1000 Base-T/TX
Ink Droplet Size	4 picoliter
Ink Capacity	130ml per color ²
Ink Droplet Size	Dye/Pigment Reactive Ink
Color Set	Dye: Cyan, Magenta, Yellow, Black Pigment: Matte Black

Buffer Ram	256MB
Media Width	Cut Sheet: 8" - 36" (203.2mm - 914mm) Roll Feed: 10" - 36" (254mm - 914mm)
Media Thickness	0.07-0.8mm (2.8-31.4mil)
Maximum Roll Print Length	Roll Feed: 59' (18 meters) ³ Cut Sheet: 63" (1.6 meters)
Maximum Media Roll Diameter	5.9" (150mm)
Borderless Printing Width	10, 14, 17, 24 B2 (20.28/515 mm), A1 (23.38/594mm), B1(728mm), A0(841mm), 36
Paper Feed Method	Roll Feed: One Roll, Top-loading, Front output Cut Sheet: One sheet, Top loading, Front output
Languages	Language: GARO (Canon Proprietary), HP-GL/2, HP-RTL
Noise Level Approx	Operation: 47 dB (A) or less Standby: 35 dB (A) or less Acoustic Power: 6.4 Bels
Physical Dimensions	42 (H) x 51 (W) x 34 (D) (with basket open)
Weight	Approximately 139lb. with stand

imagePROGRAF iPF770 MFP L36

Power Source	AC-100-240V (50-60Hz)
Power Consumption	Maximum: 140W or less Standby 5W or less Power Off: .5W or less (Compliant with Executive Order)
Operating Environment	Temperature: 59°-86° F (15°-30° C) Relative Humidity: 10-80% (No Condensation)
User-replaceable items	Print Head (PF-04)Maintenance Cartridge (MC-10)Ink Tanks (PFI-107: C, M, Y, BK, MBK)
Software Included	Canon Printer Driver, Printer Driver Extra Kit (Free Layout, Color imageRUNNER Enlargement Copy, Advanced Preview), Direct Print & Share, imagePROGRAF Print Utility ² , PosterArtist Lite (PC Only), Print Plug-in for Microsoft® Word/Excel/PowerPoint (PC only), Status Monitor, Media Configuration Tool, Optimized Module for AutoCAD ^d
	Scanner Scanner Type: Contact Image Sensor (CIS) technology Scan Accuracy: +/- 0.20% Speed: 3 ips monochrome, 1 ips color (Copy, Standard Mode) Optical Resolutions: 600 dpi Max. Document Size: Width: 38 inch document width (36 inch image width) Length: 50 inch Thickness: 0.5mm Standard Interface (Scan to USB): USB 2.0 Standard Interface (Scan to Network): Gigabit ethernet