

imagePROGRAF iPF 8400SE

SPECIFICATIONS

Printer Type	6-Color 44-inch Printer
Number of Nozzles	Total: 15,360 C, M, Y, BK, MBK, R: 2,560 nozzles each
Nozzle Pitch	1,200 dpi Non-firing nozzle detection and compensation
Print Resolution (Up to)	2,400 x 1,200 dpi (Max)
OS Compatibility	Windows® (XP/Vista/7/8), Macintosh® (OSX)
Standard Interfaces	USB 2.0 High-Speed 10/100 Base-T/TX
Ink Droplet Size	4 picoliter
Ink Capacity	330 and 700ml per color available
Ink Droplet Size	LUCIA EX Ink (Pigment based)
Color Set	Cyan, Magenta, Yellow, Black, Matte Black, Red
Buffer Ram	384 MB
Media Width	Cut Sheet: 8" - 44" Roll: 10" - 44"
Media Thickness	Front Loading Manual Feed: 0.07 - 0.8mm (2.8 - 31.4mil) Roll: 0.07 - 0.8mm (2.8 - 31.4mil)

imagePROGRAF iPF 8400SE

Maximum Roll Print Length	59 Feet (18 meters) ²
Maximum Media Roll Diameter	5.9" (150mm)
Borderless Printing Width	515mm (JIS B2), 1,030mm (JIS B0), 594mm (ISO A1), 841mm (ISO A0), 10", 14", 17", 24", 36", 42", 44"
Paper Feed Method	Roll Feed: One Roll, front output Front Loading Manual Feed: One sheet, front output
Languages	GARO (Canon Proprietary)
Noise Level Approx	Operation: 50 dB (A) or less Standby: 35 dB (A) or less Acoustic Power: Approx. 6.8 Bels or less
Physical Dimensions	45.0" (H) x 74.5" (W) x 28.9" (D)
Weight	Approximately 258lbs. with stand
Power Source	AC-100-240V (50-60Hz)
Power Consumption	Maximum: 190W or less Standby 5W or less Power Off: .5W or less (Compliant with Executive Order)
Operating Environment	Temperature: 59°-86° F (15°-30° C) Relative Humidity: 10-80% (No Condensation)
User-replaceable items	Print Head (PF-05), Maintenance Cartridge (MC-08), Durable Rotary Media Cutter (CT-06), Ink Tanks (PFI-306, PFI-706)

imagePROGRAF iPF 8400SE

Software Included

Canon Printer Driver, Printer Driver Extra Kit (Free Layout, Color imageRUNNER Enlargement Copy, Advanced Preview), PosterArtist Lite (PC Only), Print Plug-in for Microsoft® Word/Excel/PowerPoint, Accounting Manager (PC Only), Direct Print & Share, Optimized Module for AutoCAD (PC Only)