

SPECIFICATIONS

Printer Type	12-Color 60-inch Printer
Number of Nozzles	Total: 30,720 All Colors: 2,560 nozzles each
Nozzle Pitch	1,200 dpi
Nozzle Recovery System	Non-firing nozzle detection and compensation
Print Resolution (Up to)	2,400 x 1,200 dpi (Max)
OS Compatibility	Windows® (XP/Vista 32/64bit/Windows 7 32/64bit) Macintosh® (OSX)
Standard Interfaces	USB 2.0 High-Speed 10/100/1000 Base-T/TX
Ink Droplet Size	4 picoliter
Ink Capacity	330ml per color ² (Optional 700ml)
Ink Droplet Size	LUCIA EX Ink (Pigment based)
Color Set	Cyan, Photo Cyan, Magenta, Photo Magenta, Yellow, Black, Matte Black, Red, Green, Blue, Gray, Photo Gray

imagePROGRAF iPF 9400

Buffer Ram	640 MB
Hard Drive	250 GB
Media Width	Cut Sheet: 8" - 60" Roll: 10" - 60"
Media Thickness	Front Loading Manual Feed: 0.07 - 0.8mm (2.8 - 31.4mil) Roll: 0.07 - 0.8mm (2.8 - 31.4mil)
Maximum Roll Print Length	59 Feet (18 meters) ²
Maximum Media Roll Diameter	5.9" (150mm)
Borderless Printing Width	515mm (JIS B2), 1,030mm (JIS B0), 594mm (ISO A1), 841mm (ISO A0), 10", 14", 17", 24", 36", 42", 44", 50", 60"
Paper Feed Method	Roll Feed: One Roll, front output Front Loading Manual Feed: One sheet, front output
Languages	GARO (Canon Proprietary)
Noise Level Approx	Operation: 68 dB (A) or less Standby: 35 dB (A) or less

imagePROGRAF iPF 9400

Physical Dimensions

45" (H) x 90.5" (W) x 30.2" (D)

Weight

Approximately 362 lbs. with stand

Power Source

AC-100-240V (50-60Hz)

Power Consumption

Maximum: 190W or less

Standby: 6W or less

Power Off: .5W or less (Compliant with Executive Order)

Operating Environment

Temperature: 59°-86° F (15°-30° C)

Relative Humidity - 10-80% (No Condensation)

